

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► INOX



GENERAL FEATURES

- 200 Lt. Refrigerated upright
- S/S external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (60mm per side)
- Digital Thermostat
- Opening door alarm
- Removable Gasket
- Reversible door
- Doors lock fitted as standard
- Adjustable shelves: 2 Pcs + 1 Pcs Bottom
- N.2 Adjustable feet + N.2 Rollers at the back
- HIGH S/S Adjustable feet or Lockable castor as optional
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	200 L
Temperature	+0°C ~ +8°C
Consumption	0.677 kWh/24h
Rated Power	110 W
Noise level	40 dB(A)
Net Weight	34 Kg
Gross Weight	38 Kg
External Dimensions (WxDxH mm)	600x637x835
Internal Dimensions (WxDxH mm)	500x410x660
Packaging dimensions (WxDxH mm)	640x675x880
Loading quantities 20'/40'/40'HQ	54/108/162

CERTIFICATION

CE RoHS



QRX 200



GAS R600a		60 mm	A ENERGY CLASS	4 CLIMATIC CLASS	38°C

DETAILS

 Digital Thermostat	 Inner assistance fan	 Shelf with small distance between the line and bottom shelf fitted as standard
 Lock fitted as standard	 The items can be supplied either with adjustable feet or lockable castor	

PRODUCT DIMENSIONS

